

SETTING HIRE STANDARDS™

850-BL

CRAWLER SCISSOR LIFT



Technical data	Bibi 850 BL
Basket capacity	250 kg (2 op.)
Max working height	7.9 m
Max height basket floor	5.9 m
Moving height	6.1 m
Lateral levelling for moving at heights	+/- 4°
Powered	Gasoline Honda iGX390

Accelerator	Autom.
Undercarriage	Bi-Levelling
Basket levelling	Autom.
Longitudinal levelling Front	+/- 16°
Longitudinal levelling Rear	+/- 20°
Lateral levelling	+/- 15°

Direction-Control System	Yes
Easy-Drive System	Yes
Kit for high speed	max 2.20 km/h
Ground emergency	Yes
Control of inclination	Autom.
Gradeability	25°
Side slope	21°
Length	1.94 m
Width	1.30 ÷ 1.50 m
in. machine height with folded railings	1.98 m
Total weight	1990 kg
Compliance	EN 280, ANSI, CSA, ASNZS1418



BIBI, mini-crawler scissor lift able to operate at 8 m working height. The crawler traction overcomes all the standard limits of traditional 4x4 traction providing the opportunity to work in limited spaces. The automatic levelling of the machine, enables the operator to work easily and always in full safety conditions even in big slopes or uneven and rough terrain. The bi-energetic engine, thermic and electric, provides full versatility, both for inside or outside applications.

