850-HE





850-HE

Technical data	Bibi 850-HE
Basket capacity	250 kg (2 op.)
Max working height	7.8 m
Max height basket floor	5.8 m
Moving height	4.0 m
Lateral levelling for moving at heights	-
Powered	Gasoline Honda GX270
Powered (option)	Gasoline Honda iGX390
Powered (option)	Diesel Hatz 1B40
Accelerator	Manuale / Manual
Undercarriage	Retraibile Retractable
Basket levelling	Autom.
Longitudinal levelling Front	+/- 13°
Longitudinal levelling Rear	+/- 14°
Lateral levelling	+/- 23°
Power generator (option)	220V-1kW (iGX390, 1B40)
Electric pump (option)	220V-2kW
Hydraulic commands	Proporzionali Proportionals
Direction-Control System	Si / Yes
Easy-Drive System	No
Kit for high speed	max 2.20 km/h
Ground emergency	Si / Yes
Control of inclination	Autom.
Gradeability	25°
Side slope	21°
Lenght	2.14 m
Width	0.80 ÷ 1.24 m
Min. machine height with folded railings	1.88 m
Total weight	1730 kg
Compliance	EN 280 : 2015





BIBI, mini-crawler scissor lift able to operate at 8 m working height. The crawler traction overcomes all the standard limits of traditional 4x4 traction providing the opportunity to work in limited spaces. The automatic levelling of the machine, enables the operator to work easily and always in full safety conditions even in big slopes or uneven and rough terrain. The bi-energetic engine, thermic and electric, provides full versatility, both for inside or outside applications.



